

AM2202 Pure Acrylicester

- Product Overview : The AM2202 is made of special pure acrylic monomer polymerization, it is a general-purpose strong adhesion resin with good wettability on a variety of substrates, and excellent adhesion.
- Characteristics: Excellent adhesion to melamine, plastic, metal, wood, etc., moderate curing speed, strong versatility.
- Scope of application: wood coatings, wood floor coatings, PVC floor coatings, vacuum electroplating, plastic coatings, printing inks, etc
- Product Specifications.

Project	Index	Testing Standards
Appearance	Slightly yellow transparent	visual assessment
Active principle	100%	theoretical value
Acid value (mg KOH/g)	≤8.0	GB/T 6743-2008
Viscosity mpa.s/25 C°	10000-20000	GB/T 2794-2013
Functional group	2	theoretical value

- Package: 220KG/barrel, iron barrel
- Storage Requirements: Keep the resin in a cool or dry place away from light, and avoid sunlight and heat sources; the storage temperature should not exceed 40C°.
- Shelf life:At least half a year under normal conditions.
- Avoid touching skin, eyes and clothes, and wear protective gloves during operation; In case of leakage, wipe it with cloth and clean it with ethyl acetate; Please refer to MSDS for detailed instructions; Each batch of goods can be put into production only after being tested.